Electric Auto Rice Cooker





FRC54NC
Cooking Capacity:
2.8-5.0kg
Rice Pan:

Fujimak Electric Auto Rice Cookers have high thermal efficiency and incorporate a sheathed heater for strong resistance to shock and vibration.

FRC108NC

Cooking Capacity: **2.8-10.0**kg

Rice Pans:

2

DESCRIPTION OF THE PARTY OF THE


FRC162NC


Cooking Capacity: 2.8-15.0kg

Rice Pans :

3







	45 65	Power S Connec	iource tion		
	009	16	0		
-	H				
620	130				
750			215_360	600	50
		_			
gmn	₩ 402				Exhaust
		1351	u	q	Air Duct
		000			11
HIOU		10000			i
HOUS	402	10000		d	Power Souri

Model	FRC54NC	FRC108NC	FRC162NC
Overall dimensions	750(W)×600(D)×517(H) mm	750(W)×650(D)×964(H) mm	750(W)×650(D)×1381(H) mm
Power supply	3P 400V 50/60Hz	3P 400V 50/60Hz	3P 400V 50/60Hz
Heater element	5.4kW	5.4kW×2	5.4kW×3
Total power consumption	5.4kW	10.8kW	16.2kW
Rice cooking capacity	2.8 ∼ 5.0kg	2.8 ~ 10.0kg	2.8 ~ 15.0kg
Electric loading breaker	20A	40A	60A
Adjustable legs	Stainless Steel Plate ±15mm adjustable	Stainless Steel Plate ±15mm adjustable	Stainless Steel Plate ±15mm adjustable
Cooking control	Thermistor	Thermistor	Thermistor
Weight	60kg	120kg	180kg
Attachment (Round rice pan)	Teflon Coated Ø490×190(H) mm×1	Teflon Coated ∅490×190(H) mm×2	Teflon Coated Ø490×190(H)mm ×3

Exterior / Interior / Door : Stainless steel plate Heat insulation : Glass wool

^{*}The FRC-F series featuring an aluminum interior is also available. Please inquire for details.

^{*}The two-stack model is also available on a mount in which the lower device is set somewhat higher.